



# Electrak<sup>®</sup> Garden Tractor

## TRAILER SWEEPERS



### EXCLUSIVE FLIPOMATIC HAMPER



### REAR DUMP ACTION!

### SPECIFICATIONS

- **BRUSH ASSEMBLY** — made of waterproof polypropylene bristles. Highly durable, yet easily replaced. Revolves in ball bearings.
- **HAMPER** — Heavy laminated reinforced vinyl over  $\frac{3}{4}$ " plated tubular framework. Exclusive FLIPOMATIC rear dump or lift out.
- **HEIGHT ADJUSTMENT** — vertical control permits instant adjustment from operator's position on the rider/tractor for pavement or lawn sweeping (0 - 2 $\frac{1}{2}$  inches). Brushes can be raised when transporting sweeper to and from sweeping area.
- **FRONT SHIELD ASSEMBLY**—made of solid 12 ga. thick steel.
- **UNIVERSAL HITCH**—made of 1 $\frac{3}{4}$ " x  $\frac{3}{8}$ " bar steel with long tongue to permit easy attachment/good trailing characteristics—short turning radius behind all riding mowers and garden tractors.
- **FRAME** — made of two (front and back) U-shaped steel bars 1 $\frac{3}{4}$ " x  $\frac{3}{8}$ " steel.
- **WIDE SWIVEL CASTERS** — made of tough high-impact polyethylene. Sectional casters swivel under sturdy 16" gauge plated steel tubing frame.
- **WHEELS** — 10" silicon-aluminum die cast wheels equipped with semi-pneumatic wide tread tires. Built-in grease fittings. Metal pinions for positive geared drive in both wheels.
- **OVERALL WIDTH** — 46 inches
- **NET WEIGHT** — 78 pounds
- **SHIPPING WEIGHT** — 96 pounds
- **HAMPER** — 14 Bu.

General Electric Company  
Outdoor Power Equipment Operation  
Corporations Park, Bldg. 702  
Schenectady, N. Y. 12305

GENERAL  ELECTRIC